

<p align="center"><b><u>Product Specification</u></b></p> <p>Ningbo Youte Metal Products Co., Ltd.</p>	<p>P/N: <b>500100</b></p>	<p align="center"><b>A</b></p>
	<p>200 stainless steel band, Size 0.50mm * 12.70mm * 50m</p>	

### **physical properties**

width: 12.70mm      ±0.10mm

Thickness : 0.50mm      ±0.02mm

Surface : BA Bright      Camber: not to exceed 1/2 in over 8 ft span.

Edge : #5 Deburred

#### **Mechanical Properties**

Tensile : 650mpa      min

Yield : 350mpa      min

Elongation : 40%      min

Hardness : HV180-220

#### **Chemical Properties**

C:0.015      S:0.030 MAX

Cr:13.0-15.0      P:0.065MAX

Ni:1.0-3.0      Si:0.75max

Mn:8.0-12.0      Cu:1.0-2.0

N:0.075-0.25

### **product description**

**The use of Baosteel's refined stainless steel 200 material has good corrosion resistance.**

**It is characterized by high strength, good ductility, and can be manufactured in various lengths; smooth edge treatment, that is safe and easy to install. The product has a marking mark on the tie that eliminates unnecessary product waste and allows the user to quickly and accurately measure the exact tie length required for any package.**

**Stainless steel belts are packed in cartons or plastic boxes. The order quantity exceeds 500 boxes for pallet transport. Air, land and sea shipping options.**

**Our company produces strictly in accordance with ISO 9001:2015 quality system. So all materials have coded traceability before any one production process.**