

<p align="center"><u>Product Specification</u></p> <p>Ningbo Youte Metal Products Co., Ltd.</p>	<p>P/N: 500140</p>	<p align="center">A</p>
	<p>200 stainless steel band, Size 0.50mm * 25.00mm * 50m</p>	

physical properties

width: 25.00mm ±0.10mm

Thickness : 0.50mm ±0.02mm

Surface : BA Bright Camber: not to exceed 1/2 in over 8 ft span.

Edge : #5 Deburred

<u>Mechanical Properties</u>	<u>Chemical Properties</u>	
Tensile : 650mpa min	C:0.015	S:0.030 MAX
Yield : 350mpa min	Cr:13.0-15.0	P:0.065MAX
Elongation : 40% min	Ni:1.0-3.0	Si:0.75max
Hardness : HV180-220	Mn:8.0-12.0	Cu:1.0-2.0
	N:0.075-0.25	

product description

The use of Baosteel's refined stainless steel 200 material has good corrosion resistance. It is characterized by high strength, good ductility, and can be manufactured in various lengths; smooth edge treatment, that is safe and easy to install. The product has a marking mark on the tie that eliminates unnecessary product waste and allows the user to quickly and accurately measure the exact tie length required for any package.

Stainless steel belts are packed in cartons or plastic boxes. The order quantity exceeds 500 boxes for pallet transport. Air, land and sea shipping options.

Our company produces strictly in accordance with ISO 9001:2015 quality system. So all materials have coded traceability before any one production process.